



SAFETY DATA SHEET

IDENDEN SPRAYABLE VAPOUR BARRIER COATING ET-150 AF WHITE

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME IDENDEN SPRAYABLE VAPOUR BARRIER COATING ET-150 AF WHITE

PRODUCT NO. 119987

SUPPLIER BOSTIK LIMITED
COMMON ROAD
STAFFORD
STAFFORDSHIRE
ST16 3EH
+44 1785 272625
+44 1785 272650 (24 HOUR)
sds.uk@bostik.com

2 HAZARDS IDENTIFICATION

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION R52/53.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
N'-tert-butyl-N-cyclopropyl-6-(methylthio)-1,3,5-triazine-2,4-diamine	248-872-3	28159-98-0	< 1%	N;R50/53. R43.

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Remove victim immediately from source of exposure. Move the exposed person to fresh air at once. Get medical attention.

INGESTION

DO NOT induce vomiting. Get medical attention immediately.

SKIN CONTACT

Promptly flush contaminated skin with water. Promptly remove clothing if soaked through and flush the skin with water. Get medical attention if irritation persists after washing.

EYE CONTACT

Rinse the eye with water immediately. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES

Keep run-off water out of sewers and water sources. Dike for water control.

SPECIFIC HAZARDS

Fire or high temperatures create: Toxic gases/vapours/fumes of Carbon dioxide (CO₂). Carbon monoxide (CO). Hydrocarbons.

PROTECTIVE MEASURES IN FIRE

Wear self contained breathing apparatus

IDENDEN SPRAYABLE VAPOUR BARRIER COATING ET-150 AF WHITE

11 TOXICOLOGICAL INFORMATION

INHALATION

Vapour may irritate respiratory system or lungs.

SKIN CONTACT

Liquid may irritate skin.

EYE CONTACT

May cause eye irritation or physical damage

ROUTE OF ENTRY

Skin and/or eye contact.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment. Contamination of the terrestrial and aquatic environments should be avoided

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Do not allow runoff to sewer, waterway or ground.

14 TRANSPORT INFORMATION

GENERAL

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

No transport warning sign required.

15 REGULATORY INFORMATION

RISK PHRASES

R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
--------	---

SAFETY PHRASES

S2	Keep out of the reach of children
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.
S56	Dispose of this material and its container to hazardous or special waste collection point.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

16 OTHER INFORMATION

GENERAL INFORMATION

This product should be used as directed by Bostik Ltd. For further information consult the product data sheet or contact Technical Services.

INFORMATION SOURCES

This safety data sheet was compiled using current safety information supplied by distributor of raw materials.

REVISION COMMENTS

This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact Bostik Limited.

REVISION DATE: November 2008

SDS NO.: 18213

IDENDEN SPRAYABLE VAPOUR BARRIER COATING ET-150 AF WHITE

ISSUED BY

Approved EC

REVISION DATE November 2008

REV. NO./REPL. SDS GENERATED 1

DATE November 2008

RISK PHRASES IN FULL

R43 May cause sensitisation by skin contact.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.